

# POP, billboards and everything in between

Produce everything from premium-margin jobs to commercial graphics and long-term outdoor signage with the five-meter EFI™ VUTEk® GS5000r roll-to-roll UV printer.



### Point of purchase (POP) quality

- Produce premium-margin jobs with eight colors and white
- Stay ahead of the competition with dual resolution of 600 dpi (24pL) or 1,000 dpi (12pL)
- Print POP quality up to 950 ft²/hr (88 m²/hr)
- Offer high-impact applications with multilayer, white ink printing

## Billboard productivity

- Print outdoor output with Fast-4<sup>™</sup> mode at up to 2,800 ft²/hr (260 m²/hr)
- Run multiple jobs at once with multi-queue ondemand functionality
- Load up to three rolls of material with cradle-style winders for quick job turns
- Roll graphics onto core or sheet-cut for same day order-to-delivery

#### **UV** versatility

- Eight-color, Fast-4 and white ink option in one printer
- Flexible 3M Premium UV Ink with the 3M<sup>™</sup> MCS<sup>™</sup> Warranty\*
- Multi-roll printing capability on up to three 60-inch rolls
- Automated double-sided printing option for simple and accurate registration
- Back communication of audit information on every print job with bi-directional communication between the Fiery® XF and VUTEk systems
- EFI Web-to-Print and MIS/ERP integration with native JDF connectivity

# VUTEk® GS5000r

#### **Features**

- Eight-color switchable to Fast-4
- Dual resolution for true 600 dpi (24pL) or 1,000 dpi (12pL)
- Standard multi-queue functionality
- Optional white ink including multilayer print capability
- Optional double-sided printing capability
- Optional mesh kit
- Flexible 3M Premium UV Ink

#### Media/Handling

- Flexible substrates including heavy textiles and mesh up to 125 in (3.2 mm) thick
- Maximum material up to 204 in. (5.18 m) wide (maximum width of material, three rolls, including media brakes), and up to 3.6 ounces/ft<sup>2</sup> or 1,100 grams/m<sup>2</sup> thick
- Multiple-roll capability—up to three 60" rolls; maximum weight of 880 lbs. full width

### **Productivity**

- Fast-4: 2,800 ft<sup>2</sup> (260 m<sup>2</sup>) per hour
- Eight-color: 950 ft<sup>2</sup> (88 m<sup>2</sup>) per hour

#### **Environmental considerations**

- Compressed Air: 95 psi (6.7 kgf/cm²) minimum, 150 psi (10.5 kgf/cm²) maximum, at 4 cf/m (113 lpm) dry air only
- Temperature: 68° F to 86° F (20° C to 30° C)
- Humidity: 30% to 80% (non-condensing)
- Weight: 12,815 lbs. (5,813 kg)
- Height: 75.10" (190.75 cm) Width: 342.35" (869.59 cm)
- Depth: 98.56" (250.34 cm)
- Balanced Electrical: 3 phase, 50/60 Hz, 70 amps (4 or 5 wire), Delta 220 +10%, 50A (Wye 400 +10%, 50A)

#### EFI Fiery proServer

- Optimized for use with the EFI Fiery proServer
- Bidirectional communication capability between the Fiery XF digital front end (DFE) and printer allows back communication of audit information on every print job
- · Powerful production tools, such as nesting, step and repeat, scaling, cropping and tiling
- Advanced ICC color management for reliable color, quality output and proofing-quality color

#### EFI VUTEk GSr 3M Premium UV Ink

- Supplied in 5.0-liter containers
- Water- and fade-resistant; contain virtually no volatile organic compounds (VOCs); are media-independent and fast-drying; and reduce production time
- Available in cyan, magenta, yellow, black, light cyan, light magenta, light yellow, light black and white
- Fifteen-month shelf life
- EFI pigment dispersions ensure optimized size and concentration for best-in-class ink stability

#### **Enhanced Service Program (ESP)**

- EFI's industry-leading service and support program for your printer, Fiery proServer hardware and Fiery XF software
- Thirteen months of Essential coverage, with 24-business-hour (3-business-day) response
- Eligible for upgrade to:
  - Critical: Providing 8-business-hour (1-business-day) response
- ProActive: Providing 16-business-hour (2-business-day) response



Warranty

\* The 3M™ MCS™ Warranty backs graphics printed with the EFI VUTEk GS5000r printer on select 3M flexible media and printed and applied according to 3M Product and Instruction Bulletins. This warranty lasts up to five years on EFI co-branded inks that have a shelf life of 15 months.

Nothing herein should be construed as a warranty in addition to the express warranty statements provided with EFI products and services

# EFI fuels success.

From Fiery to superwide inkjet, from the lowest cost per label to the most automated business processes, EFI has everything your company needs to succeed. Visit www.efi.com or call 650-357-3500 for more information.



Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

The APPS logo, AutoCal, Auto-Count, Balance, Best, the Best logo, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, DockNet, Digital StoreFront, DocBuilder, DocBuilder Pro, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPhoto, EPRegister, EPStatus, Estimate, ExpressPay, Fabrivu, Fast-4, Fiery, the Fiery logo, Fiery Diven, the Fiery Diven logo, LapNet, Logic, MiniNet, Monarch, MicroPress, OneFlow, Pace, PhotoXposure, Printcafe, PressVu, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, Printstream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Rastek, the Raskek logo, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincrolor, Splash, Spot-On, TrackNet, UltraPress, UltraPus, UltraVes, UVTSk, the VUTEk logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.